

## Konfiguration iWay SIP Trunk auf innovaphone v13

---

Name	iWayTrunk		
Disable	<input type="checkbox"/>		
Type	Provider ▾		
Transport	UDP ▾	<input type="checkbox"/> Without registration	
AOR	Hauptnummer	@	sip.phone.iway.ch
Local Hostname	<input type="text"/>		
Local Port	5060		
Proxy	sip.phone.iway.ch		
STUN Server	<input type="text"/>		

---

- Authorization -

Username	SIP User Name		
Password	SIP Passwort	Retype	SIP Passwort

---

- Media Properties -

General Coder Preference	G711A ▾	Framesize [ms]	20	Silence Compression	<input type="checkbox"/>	Exclusive	<input checked="" type="checkbox"/>
Local Network Coder	G711A ▾	Framesize [ms]	20	Silence Compression	<input type="checkbox"/>		
Enable T.38	<input type="checkbox"/>	No DTMF Detection	<input type="checkbox"/>	Enable PCM	<input type="checkbox"/>	Media-Relay	On ▾, Video <input type="checkbox"/>
SRTP Cipher	AES128/32 ▾	SRTP Key Exchange	No encryption ▾	No ICE	<input checked="" type="checkbox"/>	No RTCP-MUX	<input type="checkbox"/>
Record to (URL)	<input type="text"/>						

---

- SIP Interop Tweaks -

Proposed Registration Interval [s]	<input type="text"/>
Accept INVITE's from Anywhere	<input type="checkbox"/>
Enforce Sending Complete	<input type="checkbox"/> (affects outgoing SIP calls only)
No Video	<input checked="" type="checkbox"/>
To Header when Sending INVITE	Called Party ▾ (affects outgoing SIP calls only)
From Header when Sending INVITE	Fixed AOR ▾